

Fall Protection

Carabiners & Extenders



FallTech connectors are tested to comply with current ANSI standards and built for a wide range of workplaces. FallTech has worked hard to make sure that when you need to be connected, you have the right equipment for the job.




8366LAF

Web with Choking Loop and D-ring.



5073H

The Triple Action SRD Connector offers a dual locking system with versatile connection options, all within a compact size, 4" x 1½" that is simple to connect and easy to use with full protection




8447

Large Twist Lock; 2 1/4" Opening; 3,600 lbs Gate; with Captive Pin Option.



8445

Compact Twist Lock; 7/8" Opening; 3,600 lbs Gate.



8450

Medium Twist Lock; 1" Opening; 3,600 lbs Gate; with Captive Pin Option.



8447A

Large Twist Lock; 2" Gate Opening; 3,600 lbs Gate; with Captive Pin Option.

Fall Protection

Carabiners & Extenders



8466A

Medium Twist Lock; 7/8" Gate Opening; 3,600 lbs Gate; with Captive Pin Option.



8366

Web with Snap Hook and D-ring.

[More](#)



8366L

Web with Choking Loop and D-ring.

Fall
Protection



83662D

Web with Snap Hook and 2nd D-ring for SRL Attachment.

Fall Protection Lifelines



FallTech connectors are tested to comply with current ANSI standards and built for a wide range of workplaces. FallTech has worked hard to make sure that when you need to be connected, you have the right equipment for the job.



8150

5/8" Premium Polyester Rope; with 1 Snap Hook and Braid-end.



8200

5/8" Premium Polyester Rope; with 1 Snap Hook and Braid-end.



8149

5/8" Copolymer Rope; with 1 Snap Hook and Braid-end.



8151

5/8" Premium Polyester Rope; Thimble and Braid-End.



8150T

5/8" Premium Polyester Rope; with 1 Snap Hook and Taped-End.



7120

Counter Weight; 5 lbs for Vertical Lifelines; Chokes to Trailing End to Keep Line Taught.

Fall
Protection

Fall Protection Lanyards



ElasTech® Shock-Absorbing Lanyards have all of the advantages of our popular Internal lanyards, plus the added benefit of elasticity to enhance worker mobility and reduce the potential for lanyard entanglement.



8240Y3

Adjustable Y-leg for 100% Tie-off; with 1 Snap Hook and 2 Rebar Hooks.



8240Y32D

Expanding Y-leg for 100% Tieoff; with 1 Snap Hook and 2 Rebar Hooks; D-ring for SRL Attachment



8240Y2D

Adjustable Y-leg for 100% Tieoff; with 3 Snap Hooks and D-ring for SRL Attachment.



8240Y

Adjustable Y-leg for 100% Tie-off; with 3 Snap Hooks.



8240Y32D2R

Adjustable Y-leg for 100% Tie-off; with 1 Snap Hook and 2 Rebar Hooks; 1 D-ring for SRL Attachment and 2 Rescue D-rings; 4' to 6' Range of fit.



8240Y3L

Adjustable Y-leg for 100% Tie-off; with Loop and 2 Rebar Hooks.

Fall
Protection

Fall Protection Lanyards



82403

Adjustable Single Leg; with 1 Snap Hook and 1 Rebar Hook.



8240

Adjustable Single Leg; with 2 Snap Hooks.



82403L

Adjustable Single Leg; with Loop and 1 Rebar Hook.



8240L

Adjustable Single Leg; with Loop and 1 Snap Hook.



8240Y3A

Adjustable Y-leg for 100% Tie-off; with 1 Aluminum Snap Hook and 2 Aluminum Rebar Hooks.



82403A

Adjustable Single Leg; with 1 Aluminum Snap Hook and 1 Aluminum Rebar Hook.

Fall Protection Lanyards



8240A

Adjustable Single Leg; with 2 Aluminum Snap Hooks.



8240YA

Adjustable Y-leg for 100% Tie-off; with 3 Aluminum Snap Hooks.



8240Y3A2R

Adjustable Y-leg for 100% Tie-off; with 1 Aluminum Snap Hook and 2 Aluminum Rebar Hooks; 2 Steel Rescue D-rings.

Fall
Protection